

| Nominal Load Rating lbs. [kg] | Model | LWB | Beam Width** (KPI) in. [mm] | Beam Drop in. [mm] | | | LMS™ Hub Option | Bearing Cone Inner / Outer* |
|----------------------------------|---------|---------|--------------------------------|--------------------|-----------|------------|-----------------|--------------------------------|
| | | | | 3.5 [89] | 3.74 [95] | 5.0 [127] | | |
| 6,000 [2,722] | D-600N | | 62.7 [1,593] | | | | N/A | 45284/25880 |
| 7,000 [3,175] | D-700N | | | | | | | |
| | D-700F | | 71.0 [1,803] | | | | | |
| 8,000 [3,629] | D-800F | | | | | | | |
| | D-800W | | 72.0 [1,829] | | | | | |
| 8,500 [3,856] | D-850F | | 71.0 [1,803] | | | | | |
| | D-850W | | 72.0 [1,829] | | | | | |
| 10,000 [4,536] | D-1001I | | 69.0 [1,753] | | | | | |
| | D-1001W | | 71.0 [1,803] | | | | | |
| 12,000 [5,670] | D-1251I | | 71.5 [1,816] | | | | | |
| | | D-1251W | | 69.0 [1,753] | | | | |
| | | | | 71.0 [1,803] | | | | |
| 13,200 [5,987] | D-1321I | | 71.5 [1,816] | | | | | |
| | | D-1321W | | 69.0 [1,753] | | | | |
| | | | | 71.0 [1,803] | | | | |
| 14,600 [6,622] | D-1461I | | 71.5 [1,816] | | | | | |
| | | D-1461W | | 69.0 [1,753] | | | | |
| | | | | 71.0 [1,803] | | | | |
| 20,000 [9,072] | D-2000F | | 68.0 [1,727] | | | | | |
| | D-2000W | | 70.66 [1,795] | | | 5.24 [133] | | |
| 22,800 [10,342] | D-2200F | | 68.0 [1,727] | | | | | |
| | D-220W | | 70.66 [1,795] | | | 5.24 [133] | | |

